


RS-1601 ROC-IT SELECTORIZED AB



WARNING!

TO PREVENT POSSIBLE TIPPING, BOLT THIS UNIT TO THE EXERCISE FLOOR. FAILURE TO DO SO MAY RESULT IN SERIOUS INJURY OR DEATH.

Note: Both Serial Number and Model Number are Required when Ordering Parts RECORD SERIAL NUMBER HERE <u>Customer Service</u>

(800) 548-5438

(858) 578-7676

<u>Fax</u>

(858) 578-9558

E10

MACHINE CODE

www.facebook.com/hoistfitness

CONTENTS

INSTRUCTIONS 02	2
FRAME ASSEMBLY 04	4
PRE-ASSEMBLY 25	3
DECAL PLACEMENT 25	5
DECAL REFERENCE	7
PART LIST 29	9
ABBREVIATIONS 32	2
BOLT SIZING CHART 33	3
WASHER SIZING CHART 34	4
MAINTENANCE SCHEDULE 30	6
GENERAL MAINTENANCE INFORMATION 3	7
WEIGHT TRAINING TIPS 38	8
EXERCISE LOG 39	9
I IMITED WARRANTY	n

INSTRUCTIONS

Before beginning assembly please take the time to read instructions thoroughly. Please use the various lists in this manual to make sure that all parts have been included in your shipment. When ordering, use part number and description from the lists. Use only HOIST replacement parts when servicing. Failure to do so will void your warranty and could result in personal injury.

HOIST equipment is designed to provide the smoothest, most effective exercise motion possible. After assembly, you should check all functions to ensure correct operation. If you experience problems, first recheck the assembly instructions to locate any possible errors made during assembly. If you are unable to correct the problem, call your authorized HOIST dealer. Be sure to have your serial number and this manual when calling. When all parts have been accounted for, continue on.

TOOLS REQUIRED

Ratchet Wrench

1/2", 9/16" and 3/4" Sockets

Adjustable Wrench

Rubber Mallet

Tape Measure


Level


Hex Key Wrench Set


Two People


THIS PAGE WAS INTENTIONALLY LEFT BLANK

PAGE 03 RS-1601 ASSEMBLY














PAGE 07 RS-1601 ASSEMBLY













































IT WILL BE NECESSARY TO LOOSEN SOME FRAME HARDWARE TO RE-ALIGN THE

FRAME AND RETIGHTEN BOLTS.









DECAL REFERENCE

15 LBS / 7 KGS 165 LBS / 75 KGS

325 LBS / 147 KGS

30 LBS / 14 KGS

185 LBS / 84 KGS

345 LBS / 156 KGS

45 LBS / 20 KGS

205 LBS / 93 KGS

65 LBS / 29 KGS

225 LBS / 102 KGS

85 LBS / 39 KGS

245 LBS / 111 KGS

105 LBS / 48 KGS

265 LBS / 120 KGS

125 LBS / 57 KGS

285 LBS / 129 KGS

145 LBS / 66 KGS

305 LBS / 138 KGS

021-0003934



021-0003113

HOISTFITNESS.COM

021-0003221






021-0003881









021-0003341



SERIAL # DECAL

TO VISIT THE HOIST® MOBILE **APPLICATION, SCAN THE QR** CODE* BELOW WITH YOUR SMARTPHONE'S CAMERA.

THE APPLICATION PROVIDES A SHORT VIDEO, ALONG WITH ANSWERS TO:

- . HOW DO I USE THIS MACHINE?
- · WHY DOES THE MACHINE MOVE?
- · WHERE IS HOIST ON THE WEB?

SCAN HERE:





* USING YOUR SMARTPHONE, VISIT WWW.HOISTFITNESS.COM/SCAN TO DOWNLOAD A FREE QR CODE SCANNER.

021-003864 (HS-1601)

021-0003864

DECAL REFERENCE (CONTINUED)





OBLIQUE CRUNCH

- Sit with back against back pad and seat in unlooked position with knees to the side of the body.
- Grasp handles and place feet behind roller pads.
- Pull handles down while pulling roller pads upward.
- 4. Slowly return to starting position.

TWISTING OBLIQUE

- Sit with back against back pad and see in unlocked position with knees to the side of the body.
- Grasp handles and place feet behind roller pads.
- Pull handles down while pulling roller pads upward.
- 4. Slowly return to starting position.

SEAT SWIVEL



SWIVEL SEAT



ROTATING CRUNCH

- Sit with back against back pad and seat in unlocked position.
- 2. Grasp handles and place feet behind roller pads
- 3. Pull handles down while rotating roller pads
- Lower and continue rotating roller pads to complete circular motion, returning to starting position.

TORSO ROTATION

- Sit with back against back pad and seat in unlocked position with knees to the side of the body.
- Grasp handles and place feet behind roller pads.
- Pull handles down and hold the crunch position while rotating roller pads from side to side,
- 4. Slowly return to starting position.







021-000382

021-0003825

HOIST

CAUTION

- Keep your hands on the handles at all times.
- Your seat is designed to move as you exercise.
- Your seat will swivel side to side unless locked.
- Do not enter or exit the machine unless it is stationary.



021-0003822

INSTRUCTIONS:

- Sit with back against back pad and seat in locked position.
 - 2. Grasp handles and place feet behind roller pads.
 - Pull handles down while pulling roller pads upward.
 - 4. Slowly return to starting position.



021-0003823-A

PART LIST

NOTE: SOME OF THESE PARTS MAY COME PRE-INSTALLED

ITEM NO.	PART NUMBER	DESCRIPTION	QTY
1	010-01C0414	RS-1601 CABLE ASSEMBLY 151.50" LG.	1
2	022-01PD2073-A	HEAD PAD ASSEMBLY	1
3	022-01PD2073-5	HEAD PAD PLASTIC BACKING	1
4	022-01PD2079-A	SEAT PAD ASSEMBLY	1
5	022-01PD2081-A	BACK PAD ASSEMBLY	1
6	022-01PD2081-5	BACK PAD PLASTIC BACKING	1
7	022-01PD2082-A	HIP PAD ASSEMBLY	1
9	022-01PDR017	ROLLER PAD Ø3.75" X 7.00" LG.	2
10	026-01X0139	ROLLER BAR ASSEMBLY 17.69" LG.	1
11	026-01X3725	TIE-ROD END RIGHT HANDED ASSEMBLY	1
12	026-01X3724	TIE-ROD END LEFT HANDED	1
13	026-01X3683	BACK PAD MOUNT	1
14	026-01X3686	CONTROL LINK	1
15	026-01X3761	LOWER PIVOTING ASSEMBLY	1
16	026-01X3762	CROSS MEMBER ASSEMBLY	1
17	026-01X3763	LOWER CROSS BAR ASSEMBLY	1
18	026-01X3783	CROSSMEMBER ASSEMBLY	1
19	026-01X3784	BENT CROSS BAR ASSEMBLY	1
20	026-01X5578	LATCH ASSEMBLY	1
22	026-01X5956	SEAT MOUNT ASSEMBLY	1
23	026-01X5599	LEFT SIDE ASSEMBLY	1
24	026-01X5600	RIGHT SIDE ASSEMBLY	1
26	026-01PL2516	SCUFF GUARD (CURVED) 8.63" LG. W/ RIVETS	2
27	019-0001003	BUMPER ∅1.50" X .625" T	4
28	011-0711001	SET SCREW: 1/4"-28 X .25" LG. (Ni)	4
29	012-0105007	1/2-20 JAMNUT RH	1
30	012-0105012	1/2-20 JAMNUT LH	1
31	014-0011001	NYLINER BUSHING: Ø 1.09" O.D. X Ø 1.00" I.D X 1.13" LG.	2
32	014-0012013	BEARING: BALL BEARING Ø2.44" O.D. X Ø1.18" I.D.	4
33	014-0012014	BEARING: FLANGELESS - 25mm I.D.	4
34	014-0012018	SNAP RING - 25mm EXTERNAL	4
35	014-0012019	SNAP RING - 30mm EXTERNAL	4
37	014-0014002	3/8-16 FLUSH MOUNT INSERT	2
39	014-0015019	7/16" EXTERNAL RETAINING RING	1
40	014-0024001	THRUST WASHER, 1"	2

PART LIST CONTINUED

NOTE: SOME OF THESE PARTS MAY COME PRE-INSTALLED

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
41	014-0101031	BUSHING: OILITE 1.50" OD X 1.00" ID X .127" THICK	1
42	014-0101017	BUSHING: OILITE FLANGED Ø1.03" ID X Ø1.38" OD X .75" LG.	2
44	018-0002017	PULLEY 6.00" OD	1
45	018-0001003	CABLE PULLEY: Ø4.50"	1
46	020-0011009	SPRING	1
48	026-01F0289	FLANGE	1
49	026-01F0307	FLANGE: 2 HOLES 6.25" X 2.50"	1
53	026-01M0239	ALUMINUM FLATHEAD CAP $ \phi$ 1.63" X .31" LG.	1
54	026-01M0836	QUICK RELEASE CABLE LOCK 1/4"	1
55	026-01M0932	ALUMINIUM CAP: Ø1.25" ID	2
56	026-01M0933	ALUMINUM RING: Ø1.25" ID	2
57	026-01M2312	END CAP: DOMED Ø2.75" O.D.	2
58	026-01M2320	END CAP: DOMED $ \phi $ 2.25" O.D.	2
59	026-01M2630	SHAFT - ∅1.181 X 3.7500 LG.	2
61	026-01M2778	SHAFT ∅.984" X 3.7500 LG.	2
62	026-01P2653	'H' PLATE	1
63	026-01P2907	HEAD BRACKET MOUNT	1
64	026-01P2929	BACK BRACKET MOUNT	2
65	026-01P4112	CABLE SHIELD	1
67	026-01PL0151	PLASTIC WASHER Ø2.50"	2
68	026-01PL0235-27	GRIP OPEN END Ø1.188" X 15.00" LG.	2
69	026-01PL0239	THUMB LATCH	1
70	026-01PL2122	OVAL-SHAPED RUBBER FOOT	4
71	026-01PL2188	ϕ .75" X .88" RUBBER TUBE	1
72	ROC-IT WEIGHT CAGE - A2	ROC-IT WEIGHT CAGE	1
73	013-1006002	5/16" SPLIT LOCK WASHER (Ni)	4
74	013-1002010	5/16" SAE FLAT WASHER (Ni)	16
75	013-1002007	3/8" X 22mm FLAT WASHER (Ni)	14
76	013-1010003	5/16" INTERNAL LOCK WASHER (Ni)	15
77	013-1006003	3/8" SPLIT LOCK WASHER (Ni)	15
81	013-1002008	1/4" X 16mm SAE FLAT WASHER (Ni)	4
82	013-1003001	3/8" FENDER WASHER (Ni)	2
83	013-1002006	1/2" X 27mm SAE FLAT WASHER (Ni)	32
85	011-0701077	1/4"-20UNC X 1.00" BHCS (Ni)	2
87	011-0701003	5/16"-18UNC X 1.00" BHCS (Ni)	13
88	011-0701004	5/16"-18UNC X 1.25" BHCS (Ni)	6

PART LIST CONTINUED

NOTE: SOME OF THESE PARTS MAY COME PRE-INSTALLED

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
91	011-0701020	3/8"-16UNC X 1.00" BHCS (Ni)	14
93	011-0702020	3/8"-16UNC X 1.00" FHCS (Ni) W/NYLON PATCH	1
95	011-0701049	1/2"-13UNC X 1.50" BHCS (Ni)	2
96	011-0116108	1/2"-13UNC X 1.25" LOW HEAD SHCS (Ni)	4
97	011-0116145	3/8"-16UNC X 1.75" LOW HEAD SHCS (Ni)	1
99	011-0116150	3/8"-16UNC X 3.00" LOW HEAD SHCS (Ni)	1
100	011-0116115	1/2"-13UNC X 3.00" LOW HEAD SHCS (Ni)	6
101	011-0116116	1/2"-13UNC X 3.25" LOW HEAD SHCS (Ni)	2
102	011-0116123	1/2"-13UNC X 5.00" LOW HEAD SHCS (Ni)	3
104	012-0504004	1/4"-20 UNC THIN NYLOCK NUT (Ni)	2
105	012-0504006	5/16"-18UNC THIN NYLOCK NUT (Ni)	2
106	012-0504005	3/8"-16 UNC THIN NYLOCK NUT (Ni)	1
107	012-0504002	1/2"-13 UNC THIN NYLOCK NUT (Ni)	18
108	012-0504003	12mm x 1.25mm THIN NYLOCK NUT (Ni)	2
110	021-0003113	DECAL PINCH POINT 1.63" X 3.25" (VERTICAL)	2
112	021-0003221	DECAL HOIST 2.50" X 9.13"	3
113	021-0003341	DECAL PINCH POINT 1.07" X 2.13" (HORIZONTAL)	1
115	021-0003934	RS WEIGHT STACK DECAL #2	1
116	021-0003560	DECAL LEVER ADJUST 2.00" X 4.00" (VERTICAL)	1
117	021-0003881	ROC-N-LOC DECALS	1
118	021-0003822	ROC-IT-AB PLACARD (LEFT)	1
119	021-0003823-A	ROC-IT-AB PLACARD (RIGHT)	1
120	021-0003825	PLACARD RS-1601 AB	1
121	021-0003864	ROC-IT QR DECAL AB	1
122	SERIAL # DECAL	DECAL HOIST SERIAL # 1.63" X 2.63"	1
125	019-0001001	PLUG BUMPER	1
126	011-0116124	1/2"-13UNC X 5.25" LOW HEAD SHCS (Ni)	1
127	026-01X5950	SWITCH LEVER	1
128	014-0015009	.375" E-CLIP	1
129	026-01M3228	PULL PIN PLUNGER	1
130	026-01PL2489	.0500" RUBBERIZED NON-SKID (BLACK), ADHESIVE BACKED	2

ABBREVIATIONS

BZ = Black Zinc

Ni = Nickel Plated

SS = Stainless Steel

WZ = White Zinc



HHB = Hex Head Bolt



FHCS = Flat Head Cap Screw




BHCS = Button Head Cap Screw



SHCS = Socket Head Cap Screw





Low Head SHCS = Low Head Socket Head Cap Screw



SHSS = Socket Head Shoulder Screw

BOLT SIZING CHART 1/4" HHB 5/16" HHB 3/8" HHB 1/2" HHB RECOMMENDED RECOMMENDED RECOMMENDED RECOMMENDED TORQUE RANGE: **TORQUE RANGE: TORQUE RANGE: TORQUE RANGE:** 6-8 ft-lbs 14-17 ft-lbs 24-30 ft-lbs 60-75 ft-lbs 5/16" BHCS 3/8" BHCS 1/2" BHCS 1/4" BHCS RECOMMENDED RECOMMENDED RECOMMENDED RECOMMENDED **TORQUE RANGE:** TORQUE RANGE: TORQUE RANGE: TORQUE RANGE: 5-7 ft-lbs 11-15 ft-lbs 19-26 ft-lbs 47-65 ft-lbs 1/4" 5/16" 3/8" 1/2" **LOW HEAD LOW HEAD** LOW HEAD LOW HEAD **SHCS SHCS SHCS SHCS** \bigcirc RECOMMENDED RECOMMENDED RECOMMENDED RECOMMENDED TORQUE RANGE: TORQUE RANGE: TORQUE RANGE: **TORQUE RANGE:** 4-6 ft-lbs 9-12 ft-lbs 18-23 ft-lbs 40-50 ft-lbs 1/4" SHCS 5/16" SHCS 3/8" SHCS RECOMMENDED RECOMMENDED RECOMMENDED **TORQUE RANGE:** TORQUE RANGE: **TORQUE RANGE:** 11-14 ft-lbs 23-29 ft-lbs 39-49 ft-lbs 3/4" 3/4" 3/ 3/4 0 1/2" FHCS 3/8" FHCS 1/4" FHCS RECOMMENDED RECOMMENDED RECOMMENDED TORQUE RANGE: **TORQUE RANGE:** TORQUE RANGE: 47-65 ft-lbs 5-7 ft-lbs 19-26 ft-lbs 3/4" 3/4" 3/4" 3/4 , ~ 0 \sim $^{\circ}$ 3/8" SHSS 5/16" SHSS 1/4" SHSS RECOMMENDED RECOMMENDED RECOMMENDED **TORQUE RANGE: TORQUE RANGE: TORQUE RANGE:** 17-22 ft-lbs 8-10 ft-lbs 3-4 ft-lbs





MAINTENANCE SCHEDULE

ROUTINE	COMMERCIAL / LIGHT COMMERCIAL MAINTENANCE	HOME MAINTENANCE	LATE	STL	DATE	EN	TRY	
Inspect; Links, Pull Pins, Snap Locks, Swivels, Weight Stack Pins	DAILY	WEEKLY						
Clean; Upholstery	DAILY	WEEKLY						
Inspect; Cables or Belts and their tension	DAILY	WEEKLY						
Inspect; Accessory Bars, and Handles	WEEKLY	3 MONTHS						
Inspect; All Decals	WEEKLY	3 MONTHS						
Inspect; All Nuts and Bolts, Tighten if needed	WEEKLY	3 MONTHS						
Inspect; Anti-Skid Surface	WEEKLY	3 MONTHS						
Clean & Lubricate; Guide Rods with a Teflon (PTFE) based lubricant (Superlube)	MONTHLY	3 MONTHS						
Lubricate; Seat Sleeves, Turcite Bushings, Linear Bearing	MONTHLY	3 MONTHS						
Clean and Wax; All Glossy Finishes	6 MONTHS	YEARLY						
Repack with Grease; Linear Bearings	6 MONTHS	YEARLY						
Replace; Cables, Belts and Connecting Parts	YEARLY	3 YEARS						

Your equipment comes with a commercial maintenance decal. For personal, in home use, please follow the home maintenance schedule listed above.

Never use ammonia, acid-based, or petroleum-based solvents on any portion of the machine as it may damage the finish.

HOIST FITNESS SYSTEMS GENERAL MAINTENANCE INFORMATION

Links, Pull-Pins, Snap Hooks, Swivels, Weight Stack Pins:

- *Check all pieces for signs of visible wear or damage.
- *Check springs in snap hooks and pull-pins for proper tension and alignment.
- *If the spring sticks or has lost its rigidity, replace it immediately.

Upholstery:

- *To ensure prolonged upholstery life and proper hygiene, all upholstered pads should be wiped down with a damp cloth after every workout.
- *Periodically take the time to use a mild soap or an approved vinyl upholstery cleaner to deter the onset of cracking or drying. Avoid using any abrasive cleaners or cleaners not intended for use on vinyl.
- *Replace ripped or warn upholstery immediately.
- *Keep sharp or pointed objects clear of all upholstery.

Decals:

*Inspect and familiarize yourself with any safety warnings or other user information posted on each decal.

Nuts and Bolts:

- *Inspect all nuts and bolts for any loosening and tighten if needed.
- *Go through a re-tightening sequence periodically to ensure that all hardware is tensioned proper.

Anti-Skid Surfaces:

*These surfaces are designed to supply secure footing and need to be replaced if they appear worn or become slippery.

Belts and Cables:

- *Hoist uses only high quality belt, and mil-spec cables.
- *Visually inspect the belts and cables for fraying, cracking, peeling or discoloration.
- *While the machine is not in use, carefully run your fingers along the belt or cable to feel for thinning or bulging areas.
- *Replace belts and cables immediately at the first signs of damage or wear. Do not use equipment until belts or cables have been replaced.

Belt and Cable Tension:

- *Referring to the Owners Manual, when belts or cables are used check all bolts attachments to be sure they are properly attached.
- *Check slack in cables and re-adjust cable tension if needed.

Seat Sleeves, Guide Rods:

- *Wipe down adjusting tubes with a dust free rag before applying lubricant.
- *Lubricate seat sleeves and Guide Rods with a Silicon or Teflon based lubricant spray.

Linear Bearings:

*Referring to the Owners Manual carefully disassemble the bearing from its housing and place a finger full of light grease (lithium, super lube, etc.) into the inside of the bearing. Using your finger, press the grease into the ball-bearings and their tracks. repeat until the ball-bearing tracks are full of grease. Insert the shaft back into the bearing and wipe off excess grease.

PLEASE KEEP THIS FOR YOUR RECORDS

WEIGHT TRAINING TIPS

Use this manual to guide you through the basic exercises you can perform on your RS-1601 HOIST® Fitness System. To gain maximum results and avoid possible injury, consult a fitness professional to develop your complete exercise program.

Always consult your physician before starting any exercise program.

To be successful in your exercise program, it is important to develop an understanding of the basic principles of strength training. Now that you have your RS-1601 HOIST® Fitness System, it is only natural that you want to get started immediately. First, determine a set of realistic goals and objectives for yourself. By deciding on an exercise plan that is right for you prior to starting, you will contribute significantly to your success.

Warm up properly before engaging in weight resistance training. Stretching, yoga, jogging, calisthenics or other cardiovascular exercise can help prepare your body for the heavier workload of lifting weights.

Learn how to perform the exercise correctly before using heavy weight. Correct form is important to avoid injury and to ensure that you work the proper muscle groups.

Know your limitations. If you are new to weight training or are embarking on an exercise regimen after a long layoff, start slowly and build foundational strength over a longer period of time.

Pay attention to your breathing. Exhale when you exert is a general rule of thumb. Never hold your breath.

Enjoy your RS-1601 HOIST® Fitness System!

Totals												Exercise	2000
												\mathbf{S}	T
												R	
												W	
												\mathbf{S}	Ī
												R	l
												W	-
												S	
												\mathbf{R}	
												W	ļ
												\mathbf{S}	l
												R	-
												W	ļ
												\mathbf{s}	1
												$\mathbf{R} \mid \mathbf{v}$	ł
												W	ļ
												\mathbf{s}	-
												R۱	ł
												W	ļ
												S	ł
												$\mathbf{R} \mathbf{W}$	ł
													ł
												S R	1
												₹ ₩	
												$\nabla \mathbf{S}$	ł
												BR	ł
												₹ ₩	$\left\{ \right.$
												$\nabla \mathbf{S}$	ł
												B	1
												W	1
												\mathbf{S}	t
												R	1
												W	1
												$ \mathbf{S} $	t
												R	1
												W	1

WEIGHT TRAINING EXERCISE LOG

S = Sets R = Repetition per set W = Weight used

HOIST FITNESS SYSTEMS LIMITED LIFETIME WARRANTY

Hoist Fitness Systems warrants this product to the **original purchaser** to be free from defects in workmanship and/or materials under normal use or service. If at any time a component part is defective, Hoist Fitness Systems shall repair or replace it (at Hoist Fitness Systems option) within a reasonable period of time. This warranty does not cover costs of removal, transportation or reinstallation. This warranty shall not apply if the defect was caused by misuse, neglect or normal wear and tear.

WARRANTY CLAIMS. All claims require: Model number, Serial number, Date of installation, and any information supporting the existence of the alleged defect.

To complete Warranty Registration visit:

www.HOISTFITNESS.com

and click on the Warranty Registration link

Starting from the original date of purchase, normal wear and tear shall be considered as the following:

COMMERCIAL USE: All malfunctions of upholstery, grips, and coatings that occur up to one year; all malfunctions of belts, or cables up to one year; all malfunctions of pulleys, bearings, or bushings that occur up to three years. The frame and body components are warranted for ten years, with structural moving parts warranted for five years.

LIGHT COMMERCIAL USE: All malfunctions of upholstery, grips, and coatings that occur up to one year; all malfunctions of belts, or cables up to one year; all malfunctions of pulleys, bearings, or bushings that occur up to three years. The frame and body components are warranted for ten years, with structural moving parts warranted for five years.

HOME USE: All malfunctions of grips, paint, and chrome that occur up to ten years; all malfunctions of electronic components, belts, cables, or upholstery that occur up to ten years; all malfunctions of pulleys, bearings, or bushings that occur up to ten years. The frame and all welded components are warranted for the life of the product.

PLEASE NOTE THAT NOT ALL HOIST PRODUCTS ARE MADE FOR COMMERCIAL USE. Refer to the instructions page of your owners manual or consult with you fitness product dealer to establish if a product is made for commercial use or not. Using a non-commercial product in a commercial setting can result in serious injury or death! Hoist Fitness Systems sole responsibility shall be to repair or replace the component within the terms stated above. Hoist Fitness Systems shall not be liable for any loss or damage of any kind including any incidental or consequential damages resulting, directly or indirectly from any warranty expressed or implied or any other failure of this product.

LIGHT COMMERCIAL USE: Our Light Commercial warranty applies to facilities that **DO NOT** charge monthly membership dues and where the equipment would be used by **no more than 50** people per day. Examples of Light Commercial facilities include hotels, apartment complexes, personal training studios, fire stations, police stations, etc., that meet the criteria stated above.

WHAT IS NOT COVERED BY THIS WARRANTY: Hoist's sole obligation under this warranty is limited to either repair or replacement of parts, subject to the additions below. This warranty neither assumes nor authorizes any person to assume obligations other than expressly covered by this warranty.

NO CONSEQUENTIAL DAMAGES: Hoist is not responsible for economic loss; profit loss; or special, indirect, or consequential damages.

WARRANTY IS NOT TRANSFERABLE: This warranty is not assignable and applies only in favor of the original purchaser/user to whom delivered. Any such assignment or transfer shall void the warranties herein made and shall void all warranties, expressed, implied or statutory, except the one (1) and five (5) year warranties described above. These warranties are exclusive and in lieu of all other warranties, including implied warranty and merchantability or fitness for a particular purpose. There are no warranties which extend beyond the description on the face hereof.

TRANSPORTATION COSTS: Hoist will accept parts covered under this warranty freight collect, provided that shipment has received prior approval. Hoist is not responsible for any other transportation costs, but will ship freight collect parts either repaired or replaced under these warranties.

Hoist Fitness Systems 11900 Community Rd. Poway, CA. 92064 (800)548-5438

PLEASE KEEP THIS FOR YOUR RECORDS